

## FEATURES

- Stainless steel IP68/IP69k single point load cell
- Suitable for platform, belt scales and other weighing devices
- Maximum platform size 800 x 800mm (for 100- 500 kg)
- Maximum platform size 400 x 400mm (for 10 - 50 kg)
- 10kg only available with PTB certificate D09-10.06 Revision 1 of C R60/2000 DE1-10.02
- 10kg, 20 kg, 50 kg also available with C4MR approval with PTB certificate D09-10.06 revision 1, C of C R60/2000 DE1-10.02 (Y=40000 Z=6000)



## AVAILABLE MODELS

xxkg	C3/C3MR/C4MR/A6S/A6M/B10S/B10M	BM6G-xx-xxkg-3B
xxkg	C3/C3MR/C4MR/A6S/A6M/B10S/B10M	BM6G-xx-xxkg-3B-S1
NTEP A6S/A6M/B10S/B10M Certificate (20kg-500kg) OIML Certificate (10kg-500kg C3/C3 MR Class) OIML Certificate (10Kg-50kg C4 Class)		



Certificate no. 12-017

test certificate no. TC8011 revision 0  
C of C no R60/2000-NL1-11.29

## SPECIFICATIONS


Capacity	kg	10 / 20 / 50 / 60/75 / 100 / 150 / 200 / 300 / 400 / 500/ 600			
		C3	C4	A6M	A6S
Accuracy class		OIML R60 C3	OIML R60 C4		
Maximum number of load cell intervals (nLC)		3000	4000		
Ratio of minimum LC verification interval $Y = E_{max} / V_{min}$		10000	15000	15000	20000
Combined error	%FS	±0.0200	±0.0173	±0.0113	±0.009
Creep	%FS/30min	±0.0245	±0.0184	±0.0184	±0.008
Temperature effect on sensitivity	%FS/10°C	±0.0117	±0.0088	±0.0088	±0.006
Temperature effect on zero	%FS/10°C	±0.0140	±0.0093	±0.0093	±0.007
Output sensitivity (=FS)	mV/V	2.0 ±0.2			
Input resistance	Ω	10kg/ 20kg/ 50kgSE/ 75kgSE/ 100kgSE		100kg~600kg	
Output resistance	Ω	380±15		351±3.5	350±3.5
Insulation resistance	MΩ	≥ 5000 (50VDC)			
Zero balance	%FS	±2.0			
Compensated temperature	°C	-10~+40			
Operating temperature	°C	-35~+65			
Storage temperature	°C	-40 ~ +70			
Excitation, recommended voltage	V	5~12 (DC)			
Excitation maximum	V	18 (DC)			
Safe overload	%FS	150			
Ultimate overload	%FS	300			
Recommended torque on fixation	N.m	10kg/20kg/50kgSE/75kgSE/100kgSE		100kg~600kg	
		10		20	
Ingress protection (according to EN 60529)		IP68/IP69K			
ATEX classification (optional)		II1G Ex ia II1C T4	II1D Ex iaD20 T73°C	II3G Ex nL II C T4	

Note: "S1" output sensitivity is 2.0±0.002mV/V

## OUTLINE DIMENSION MM(INCH)



## WIRING



- Adopt shielded, 6 conductor cable: Φ5mm
- Standard cable length: 3m